Perl Short Course

Second Session

Duncan C. White
dcw@doc.ic.ac.uk

- In this second session, we'll go over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.
- We'll broadly follow the order of material presented in Randal Schwartz's excellent introduction **Learning Perl** (the Llama book).
- We'll look at **scalar data** (numbers, strings, variables and expressions), **control structures**, **simple file input/output**, **arrays and lists** and **hashes**.
- Next session, we'll look at more complex bits of the language: **more complex file I/O** and **regular expressions**.
- In the remaining sessions, we'll look at **functions**, **references**, **modules**, **objects and classes**, take a quick tour of some of Perl's standard library and find out how to write modules.

A Note on Perl History

- **Perl 1** - **Perl 3**, 1987-89: Larry Wall designed the **Practical Extraction and Report Language** for his own amusement, and released one version of Perl per year. Note: Perl will be 20 years old on Dec 18th 2007!
- **Perl 4**, 1991-1996: the first widely used version of Perl. The final release was **Perl 4.036**, development then stopped.
- **Perl 5**, 1994-now: Larry Wall completely rewrote the perl interpreter, and added significantly to the Perl language. **Perl 5** has been maintained, patched and extended for over a decade, with new features being added every year or two. The most recent production version is **Perl 5.8.8**. Here at DoC, we have various **Perl 5.8.x** versions installed on Linux, Windows XP, Mac OS and Solaris. To find out the version installed, do **perl -v**.
- **Perl 5.10**, 2003-now: The Perl5 developers have been working on the experimental **Perl 5.9** for several years, and are just about to release **Perl 5.10** in the next couple of weeks.
- **Perl 6**, 2001-????: The Perl developers are also working on a fundamental redesign of Perl - **Perl 6** - very different internally from Perl 5. However, it never seems to get finished! Will it ever?

Scalar Variables and Values

- Let us start by looking at simple scalar variables.
- A scalar variable is written as `$variablename` - the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variable}`, just like in the Unix shell. The two forms are identical.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.
  - A reference to another variable.
- Integer literals may be written in decimal, octal or hexadecimal:

  eg. `-129, 0377 and 0xffe0.`
- Real literals may be written in *exponential notation*, with or without a *decimal point*:

  eg. `6.27, -2.4e30, 7e-5.`
- A string literal can be either delimited with single-quotes or double-quotes. Entirely different rules apply inside the two kinds of string.

Single-Quoted Strings

- A single-quoted string literal, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks. The shortest possible single-quoted string is just `''`.
- The quotes themselves are not actually part of the string - rather, they *delimit* both ends of the string.
- Each character inside the quotes is placed into the string exactly as-is - even a newline!
- There are only two exceptions to this:
  - A single-quote on it's own would terminate the current string - so to embed a single quote inside a single-quoted string, write `\'`.
  - A backslash itself may be embedded inside a single-quoted string by writing `\\`.
- Apart from backslashed single quotes and backslashed backslashes, nothing is modified inside a single quoted string.
- In particular, `$` symbols are embedded as-is, and even the C-style backslash escapes such as `\n` do not function inside a single-quoted string.

Double-Quoted Strings

- A double-quoted string literal, like `"hello $name\n"`, is much more powerful. Again, it is an arbitrary sequence of characters, but this time inside double quotes. As before, it can be split across lines (ie. contain internal literal newlines!).

- However, the backslash can now specify several important control or *escape* operations as follows:

`\n`	Newline
`\t`	Tab
`\r`	Carriage Return
`\a`	Ring bell
`\075`	Any octal ASCII value (in the above example, 7*8+5 = 61)
`\x6d`	Any hexadecimal ASCII value (in the above example, 6*16+13 = 109)
`\\`	Backslash
`\$`	Dollar
`\"`	A double-quote
`\l`	Lower-case the next letter
`\u`	Upper-case the next letter
`\L`	Start lower-casing the rest of the string
`\U`	Start upper-casing the rest of the string
`\E`	Stop `\L` or `\U`

- In addition, `$` has a special meaning when followed by a sequence of characters looking like a variable name.

- Perl gathers the longest possible sequence of variable name characters up, and replaces the entire sequence with the value of that variable.

- This process is called **variable interpolation**.

- So, for instance, `"hello $name\n"` is a string literal, comprising:
  - the character sequence `'h','e','l','l','o',' '`
  - the current value of the variable `$name` (if `$name` is not in use, then the value is the empty string),
  - the ASCII newline character (symbolically written as `\n`).

- Suppose we wish to print the value of a variable (eg. `$n`), immediately followed by a sequence of characters (eg. `"th"`) that could also form part of the variable name. If we just write:

```
"you're the $nth person today..\n"
```

  Perl will look for a variable called `nth` instead, and end up interpolating the empty string!

- To prevent this, use `{}` around the variable name:

```
"you're the ${n}th person today..\n"
```


Arbitrarily Delimited Strings

- In double-quoted strings, you still need to backslash double quotes to embed them into a string. You can also write a string obeying all the double-quoted rules, but choose your own quote character (delimiter):

```
$contentslink = qq!
<a href="contents.html">
   <img src="contents.gif" alt="Back to Contents">
</a>
!;
```

- After the `qq`, the next character (the exclamation mark) is taken as the quote character. All characters after this are placed into the string (with interpolations and backslashes working exactly as in a double-quoted string) until the next exclamation mark is encountered.

- If the opening quote is an open bracket of some kind (round, curly or square), Perl uses the appropriate closing bracket as the closing quote - We could write the above as:

```
$contentslink = qq(
<a href="contents.html">
  <img src="contents.gif" alt="Back to Contents">
</a>
);
```


Expressions

- Expressions in Perl are very like those of C, but without the pointer operators.

- Some operators expect numbers, others expect strings. Perl is sufficiently liberal to convert one to the other when needed. Thus a string such as `"17.3e7"` will convert to the number `17.3e7` when needed, and a number such as `31.53` will convert itself to the string `"31.53"` when needed.

Numeric Operators

- Perl provides all the obvious **+**, **-**, *****, **/** arithmetic operators just as you'd expect. For instance:

```
25 + 7              3 * 12.1
4.7 - 3.1           14 / 2.1
```

- Unlike C, *all operators operate in floating point*.

- Unlike both C and Pascal, Perl provides the *exponentation operator* (written ******). For example: `3.25 ** 4` (ie. 3.25^4).

- Like C, Perl provides a *modulus* operator: `10%3` gives the remainder when 10 is divided by 3. Both values are truncated to integers before this operator is applied.

- Perl provides a set of numeric comparison operators just like C: `<`, `<=`, `==`, `>=`, `>` and `!=` (not equals).

String Operators

- Strings can be *concatenated* with the fullstop operator (**.**) - for example:

  ```
  'hello ' . $name . "\n"
  ```

  (Warning: No space is added automatically between the strings!)

- Concatenation is not used as much as you would expect - interpolation is often used instead. The above example would normally just be written as:

  ```
  "hello $name\n"
  ```

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.

  One of the commonest mistakes is to compare numbers with **eq** or strings with ==. Strings and numbers are converted back and forth very easily.

  Consider `"0" == "000"` (both are converted to numbers and compared numerically, hence the comparison succeeds) and `0 eq "000"` (0 is converted to the string `"0"` which is not the same string as `"000"`!)

- Another useful string operator is the *repetition* operator (written **x**):

  `"fred" x 3` gives the result `"fredfredfred"`

  The right-hand argument is truncated to an integer before the replication occurs.

Operator Precedence and Associativity

- Each operator (in any language) has two properties: *precedence* and *associativity*.

- *Precedence* governs what happens when several operators compete for operands:
  - Consider $3 + 4 * 5$. Is that $(3 + 4) * 5 = 35$, or is it $3 + (4 * 5) = 23$ as our maths intuition suggests?
  - In fact, the latter is the case (your intuition is almost always respected!). This means that * has a *higher precedence* than +.

- *Associativity* governs what happens when operators of the same precedence compete for operands:
  - Consider $2 * *3 * *2$. Is that $(2^3)^2$ or is it 2^{3^2}? They have considerably different answers: the former gives $8^2 = 64$ whereas the latter gives $2^9 = 512$.
  - So does ** associate to the *left* or to the *right*? (the answer is *right*).

- The full precedence and associativity tables may be found in either the Camel or Llama Books.

- If your intuition fails you, *just put things in* `()`. This causes the innermost expression to be evaluated first.

Assignment

- Perhaps the most vital operator of all is assignment (=). For example:

  ```
  $x = 37;
  $y = $x * 7 + 5;
  $z = $z * 3;
  ```

  - The first simply sets `$x` to 37.
  - The second calculates `$x * 7 + 5` (using the current value of `$x`) and then stores the result in `$y`.
  - The last example takes the current value of `$z`, multiplies it by three, and stores the result back in `$z`.

- An assignment also has a value, which means it can be used like:

  ```
  $y = 5 * ($a = 7 + $x);
  $x = $y = 17;
  ```

  - The first example means: evaluate `7+$x` and store the result in `$a`, then multiply `$a` by 5 and store the final result in `$y`.
  - The second example sets both `$x` and `$y` to 17.

Binary Assignment Operators

- Assignments like `$z = $z * 3` are so common that Perl (just like C) provides a set of assignment operators that modify a single variable.

- Nearly any binary operator that computes a value can have an = sign appended on the end. For instance:

  ```
  $z *= 3;                    $sum += $element;
  ```

  These read very intuitively as *multiply* `$z` *by 3*, and *add* `$element` *to* `$sum`.

- The same works for strings: `$z .= $a;` appends the contents of `$a` onto the end of `$z`.

- Just like basic assignment, all the binary assignment operators return a value too. So the following is valid:

  ```
  $a = 3;
  $b = ($a += 4) * 7;
  ```

- **However**, never change the same variable inside two parallel branches of the same expression. The following is extremely unclear and should be avoided:

  ```
  $a = 3;
  $b = ($a += 4) * ($a -= 2);
  ```

Autoincrement and Autodecrement

- We have already seen that the common operations `$a = $a + 1` and `$a = $a - 1` can be written as `$a += 1` and `$a -= 1` In fact, there's an even easier way of doing it (taken straight from C):

  ```
  $a++;                    $a--;
  ```

  These mean simply *increment* and *decrement* `$a`.

- In fact, Perl has a prefix and postfix form of these operators: `++$a`, `$a++`, `--$a` and `$a--`. Both forms increment (or decrement) the variable in the same way.

- The difference lies in what value is returned as the expression result. Consider the following:

  ```
  $a = 7;                  $a = 7;
  $b = ++$a;               $b = $a++;
  $c = $b--;               $c = --$b;
  ```

  - In both cases, `$a` ends up as 8.
  - However, the left example increments `$a` to 8 and then assigns 8 to `$b`.
  - By contrast, the right example assigns the old value of `$a` (7) to `$b` and only then increments `$a` to 8.

- And what happens to `$c` in both examples? Work it out!

Some Simple I/O

Computation is useless without being able to get parameters and report results. For now, lets consider getting input from the keyboard, and reporting results to the screen.

Reading a line of input:

- The <> operator (pronounced *diamond* or *getline*) fetches a line of input from a file. `STDIN` is just such a file, and represents the keyboard.

- So the following:

  ```
  $name = <STDIN>;
  ```

  reads an entire line of input, up to and including a newline, and then stores the input in the variable (including the newline).

- But what if there's no more input? Files have a concept of *end of input*, when you read the last line of data from the file!

- But so does the keyboard (slightly less obviously). On Unix systems, keyboard end-of-input is signalled by the user typing CTRL-D on a line on its own. ie. one line ends with newline as normal and the very next character encountered is a CTRL-D.

- No CTRL-D character (ASCII code 4) is delivered; the CTRL-D is interpreted by the terminal driver as a signal to end the keyboard input for that process.

- When end of input occurs, <> can read no data. Not even a newline will be found. <> then, reasonably enough, returns the *empty string*.

- Because the newline is always left in a non-empty input line, an input line can only be completely empty when the input is exhausted - so comparing the result of <> against the empty string will determine when the end of input occurs.

Chop and Chomp

- Frequently, after reading a line, you want to get rid of the trailing newline.

- There are two operators we can use:
  - Perl 4 provided `chop($name)` which simply removes the last character from the named variable and returns the character removed.
  - Perl 5 added `chomp($name)` which only deletes the last character if it's a newline!

- I strongly recommend that you use chomp everywhere; it's safer and also slightly more portable (it will remove the newline from the string even if the newline convention on the OS you're using is not a single character!).

Printing the results:

- There is a nice simple way of printing some results:

  ```
  print expression;
  ```

- Combined with the variable interpolation we've seen in strings, this gives us all the power we need for now. This gives us the simplest debugging strategy in Perl, as in:

  ```
  print "debug: x=$x, y=$y, z=$z\n";
  ```

- Here's an example, allowing you to investigate different expressions:

  ```
  print "Please enter x: ";
  $x = <STDIN>;
  chomp $x;
  print "Please enter y: ";
  $y = <STDIN>;
  chomp $y;
  $z = $x + $y;
  print "\n$x + $y = $z\n";
  ```

- You may like to spend some time trying some examples of expressions, starting with the above example and incorporating different, more complex, expressions.

- Try various += and ++ types of operators to get clear exactly what they do.

Boolean Expressions

- Expressions used in a boolean context (which we'll see in a moment) are evaluated in the usual way as numbers or strings.
- Then, when the single result value is produced (a number or a string), a *zero value or empty string* is interpreted as *false*, and *anything else is true!*

  There are a few boolean operators that we haven't mentioned so far:
- `!` is a unary operator meaning *not*.
- `||` and `&&` come straight from C – `||` is pronounced *or* and `&&` is pronounced *and*.
- Just like C and Java (but unlike Pascal), these operators are *short-circuit*:
  - Consider:

    ```
    $a < 7 || $b > 6
    ```

    If `$a` is less than 7, then the whole expression is bound to be true. There is no point in evaluating the rest of the expression - so Perl doesn't!
  - Similarly, consider:

    ```
    $s eq "hello" && $t ne "bonjour"
    ```

    If `$s` is not `"hello"` then the whole expression must be false. Again, there's absolutely no point in evaluating the second half.

Statements and Control Structures

- Perl allows any expression to be made into a statement simply by appending a `;`. That is, `3;` is a valid statement, albeit a rather silly one.

  It means *evaluate the expression* (giving 3 as the result) and then *discard the final result*.
- Usually, the expressions that we tend to make into statements are ones that have side-effects:
  - Assignments (the basic `=`, all the binary assignment operators like `*=`, and the `++` and `--` operators.
  - Procedure/subroutine calls. We'll see these next session.
- Perl also provides *modifiers* for single statements:

  ```
  <statement> if <expr> ;
  <statement> unless <expr> ;
  <statement> while <expr> ;
  <statement> until <expr> ;
  ```

  (Perl allows `unless` to be used as a synonym for `if !`, ie. *if not true*, and `until` as a synonym for `while !`).
- A sequence of statements may be enclosed inside `{}` braces forming a group called a *block*. There is no `;` after the `}` of a block.

- Perl provides a conventional **if.. elsif.. elsif.... else** statement, to choose between two or more alternatives:

  ```
  if( $i < 20 || $j > 7.4 )
  {
          print "case one\n";
  } elsif( $i > 40 && $j > 0 )
  {
          print "case two\n";
  } else
  {
          print "case three\n";
  }
  ```

  Note that the brackets – both round and curly – are compulsory on an **if** - and the loop below.
- In a rare omission, Perl does **NOT** provide a special case/switch statement for multi-way comparisons. Perl 5.10 and Perl 6 will, and an add-on module exists that adds this facility.
- Perl also provides a conventional *test at the top* while loop:

  ```
  $w = $x;
  $h = 1;
  while ( abs($w-$h) > 0.001 )
  {
          $w = ($w+$h)/2;
          $h = $x/$w;
  }
  ```


- In fact, the above algorithm happens to find the square root of a number!
- Perl provides a *test at the bottom* loop, two forms:

  ```
  do {
          $y *= $x;
          $x += 2;
  } while( $x < 15 );
  ```

  ```
  do {
          $y *= $x;
          $x += 2;
  } until( $x >= 15 );
  ```
- A C-style *counting loop*:

  ```
  for( $sum = 0, $i = 1; $i <= 10; $i++ )
  {
          $sum += $i;
  }
  ```
- A very useful *for each element in a list/array* loop:

  ```
  foreach $x ( 1, 3, 7, 5, 4, 54 )
  {
          $total += $x;
  }
  ```

  (We'll see more about arrays shortly).
- Exercise: Try writing a little Perl program that reads in a number and computes the square root using the while loop on the previous page, printing out a message like `"The square root of $x is $w"` at the end.

Arrays and Lists

- An array is an ordered collection of scalars (strings or numbers). Just as all scalar variable names start with `$`, all array variable names start with `@`.
- A typical array such as `@fred` is *not the same as* `$fred`. Perl keeps the namespaces of arrays and scalars separate.
- An array may be built up piece by piece, using the following syntax:

```
$fred[0] = "hello";
$fred[1] = 7.1+$a;
$fred[2] = 17.3;
$fred[3] = $c;
```

  Note that:

  - Array indices start at 0, like C, C++ and Java, but unlike many other languages.
  - Each element of the array is a scalar, which is why an individual element of `@fred` is accessed using `$fred[expr]` not `@fred[expr]`. This is admittedly confusing!

- Assigning to an element beyond the current end of the array causes the array to be silently extended. All intervening elements are made the undefined value (looks just like 0).

- A single item may be extracted from an array by using `$name[expr]` on the RHS of an expression:

```
$sum += $fred[$i];
```

  The index expression will be truncated to an integer before the array is accessed.

- Building an array piece by piece is a bit of a pain. You can write a comma-separated list of scalar expressions inside a pair of brackets:

```
( "hello", 7.1+$a, 17.3, $c )
```

- As a special convenience inside a list, the `..` operator can be used as in `( 1..20 )` or `( 'a'..'z' )`.
- Such a literal can be assigned straight into an array variable (notice the `@` this time):

```
@fred = ( "hello", 7.1+$a, 17.3, $c );
```

- If you have a list of single words, Perl provides an special convenient syntax. Instead of:

```
@fred = ( "hello", "there", "how", "are", "you" );
```

  you can simply type:

```
@fred = qw(hello there how are you);
```


- You can also break up an array into a list:

```
( $a, $b, $c ) = @fred;
```

  This copies the element `$fred[0]` to `$a`, `$fred[1]` to `$b` and so on. Any remaining elements are quietly ignored.

- An array can be used to soak up the remainder:

```
( $a, $b, @c ) = @fred;
```

- This gives you a very easy swap operation. In most language, a temporary variable is needed. For example, in Pascal:

```
procedure swap( var x, y : integer );
var t : integer;
begin
    t := x;
    x := y;
    y := t;
end;
```

- In Perl, you can write:

```
( $x, $y ) = ( $y, $x );
```

- In this respect, Perl arrays also act as Prolog-style tuples, where similar things are possible.

Hashes - Associative Arrays

- Hash variable names start with `%`. Again, Perl is capable of keeping a hash called `%fred` entirely distinct from `$fred` and `@fred` - they all occupy separate namespaces.
- A hash *associates* one arbitrary scalar (the *value*) with another scalar (the *key*).
- A hash literal can be written as a list of pairs with the special `=>` operator:

```
%roomno = (
     "dcw"  => "225",
     "apgs" => "358",
     "psc"  => "220"
);
```

- The first element in each pair is the key, and the second is the value.
- A hash is really like a two-column table, indexed on the key field:

Key	Value
dcw	225
apgs	358
psc	220
....	....

- Hashes have a highly efficient internal indexing system (a hash table, hence the name) built in, so that you can look up a particular entry by it's key in a very few low-level operations.

- To add a single *(key, value)* pair into a hash, do:

```
$roomno{"sue"} = "569";
```

- As a convenience, Perl allows you to omit the quotes on a literal key string, and write:

```
$roomno{sue} = "569";
```

- To check whether a key exists in the hash, use:

```
if( exists $roomno{bobgeldof} ) ...
```

- To delete a single (key, value) pair from a hash:

```
delete $roomno{dcw};
```

- Alternatively, the entire hash may be cleared by:

```
%roomno = ();
```

- Our original hash literal example could thus be written as:

```
%roomno = ();
$roomno{dcw}  = "225";
$roomno{apgs} = "358";
$roomno{psc}  = "220";
```


- To retrieve a particular element from a hash, use `$room = $roomno{$person};`

  If no value has been stored against the key `$person`, the undefined value is returned, looking just like an empty string as usual.

- To process an entire hash, you can use the **keys()** functions:

```
foreach $k (keys(%roomno))
{
    $v = $roomno{$k};
    print "$k in room $v\n";
}
```

- Note that `keys(%roomno)` actually builds an ordinary array containing the keys of `%roomno`. This is potentially huge!

- Note also that the keys do not come out in any predefined order - certainly not alphabetical order, or insertion order! They come out in an efficient internal order! Because of this, you often see:

```
foreach $k (sort keys(%roomno))
...
```

- Very occasionally, you only need the **values**:

```
foreach $v (values(%roomno))
{
    print "room value $v\n";
}
```


- If you need both keys and values, the preferable (most efficient) loop uses the **each()** function and a **while** loop which iterates over all the (key, value) pairs:

```
while( ($k,$v) = each(%roomno) )
{
    print "$k in room $v\n";
}
```

- Once again, let us stress that **keys(), values()** and **each()** produces results in whatever *order* Perl likes. You cannot rely on any particular order - in particular, it will not be in sorted order, or in the order items were inserted!

- Exercise: Try building yourself a Perl program that has a set of (username, roomno) pairs in a hash, and then repeatedly reads usernames - from stdin, or a text file, as you like - until the end-of-input is reached, looking up the corresponding room number for each name and printing it out.

- Then replace the set of names and their associated room numbers with an external data file, reading them in and then building the in-memory hash. (At this early stage in your Perl knowledge, you might need to store usernames and room numbers on adjacent lines in the file).

- Next, replace the hash altogether with a dbm file (with a separate initialization program that reads the names and room nos from a text file, and stores them in the dbm-tied hash).