Perl Short Course: Second Session

Duncan C. White (d.white@imperial.ac.uk)

Dept of Computing,
Imperial College London

December 2011

- In this second session, we'll start going over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.

- In this second session, we'll start going over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.
- We'll broadly follow the order of material presented in Randal Schwartz's excellent **Learning Perl** (Llama book).

- In this second session, we'll start going over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.
- We'll broadly follow the order of material presented in Randal Schwartz's excellent **Learning Perl** (Llama book).
- We'll look at **scalar data** (numbers, strings, variables) and **expressions**, **control structures** and **input/output**.

- In this second session, we'll start going over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.
- We'll broadly follow the order of material presented in Randal Schwartz's excellent **Learning Perl** (Llama book).
- We'll look at **scalar data** (numbers, strings, variables) and **expressions**, **control structures** and **input/output**.
- Next session, we'll look at more complex bits of the language: **arrays and lists** and **hashes**, **special variables** and **regular expressions**.

- In this second session, we'll start going over Perl in more detail, going through most important parts of the language, with lots of practical examples for you to try later.
- We'll broadly follow the order of material presented in Randal Schwartz's excellent **Learning Perl** (Llama book).
- We'll look at **scalar data** (numbers, strings, variables) and **expressions**, **control structures** and **input/output**.
- Next session, we'll look at more complex bits of the language: **arrays and lists** and **hashes**, **special variables** and **regular expressions**.
- In the remaining sessions, we'll look at **functions**, **references**, **modules**, **objects and classes**, take a quick tour of some of Perl's standard library and find out how to write modules.

- **Perl 4**, 1991-1996: the first widely used version of the **Practical Extraction and Report Language**.

- **Perl 4**, 1991-1996: the first widely used version of the **Practical Extraction and Report Language**.
- **Perl 5**, 1994-now: Larry Wall completely rewrote the perl interpreter, and added significantly to the Perl language. **Perl 5** has been maintained, patched and extended for 15 years, with new features being added every year or two.

- **Perl 4**, 1991-1996: the first widely used version of the **Practical Extraction and Report Language**.
- **Perl 5**, 1994-now: Larry Wall completely rewrote the perl interpreter, and added significantly to the Perl language. **Perl 5** has been maintained, patched and extended for 15 years, with new features being added every year or two.
- **Perl 5.10**, 2003-2010: Larry and a band of developers worked on a new version of Perl 5 for several years and released **Perl 5.10** in 2007. Perl 5.10 is installed on DoC lab machines (Linux and Windows). To find out the version installed, do **perl -v**.

- **Perl 4**, 1991-1996: the first widely used version of the **Practical Extraction and Report Language**.
- **Perl 5**, 1994-now: Larry Wall completely rewrote the perl interpreter, and added significantly to the Perl language. **Perl 5** has been maintained, patched and extended for 15 years, with new features being added every year or two.
- **Perl 5.10**, 2003-2010: Larry and a band of developers worked on a new version of Perl 5 for several years and released **Perl 5.10** in 2007. Perl 5.10 is installed on DoC lab machines (Linux and Windows). To find out the version installed, do **perl -v**.
- The Perl developers now do annual releases of Perl with even numbers; odd numbered versions are development releases. **Perl 5.12** was released in April 2010, and **Perl 5.14** in May 2011.

- **Perl 4**, 1991-1996: the first widely used version of the **Practical Extraction and Report Language**.
- **Perl 5**, 1994-now: Larry Wall completely rewrote the perl interpreter, and added significantly to the Perl language. **Perl 5** has been maintained, patched and extended for 15 years, with new features being added every year or two.
- **Perl 5.10**, 2003-2010: Larry and a band of developers worked on a new version of Perl 5 for several years and released **Perl 5.10** in 2007. Perl 5.10 is installed on DoC lab machines (Linux and Windows). To find out the version installed, do **perl -v**.
- The Perl developers now do annual releases of Perl with even numbers; odd numbered versions are development releases. **Perl 5.12** was released in April 2010, and **Perl 5.14** in May 2011.
- **Perl 6**, 2001-????: The Perl developers are also working on a fundamental redesign of Perl - **Perl 6** - very different internally from Perl 5. However, it never seems to get finished! Will it ever?

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.
  - A reference to another variable.

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.
  - A reference to another variable.
- Integer literals may be written in decimal, octal or hexadecimal: eg. `-129, 0377 and 0xffe0.`

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.
  - A reference to another variable.
- Integer literals may be written in decimal, octal or hexadecimal: eg. `-129, 0377 and 0xffe0.`
- Real literals may be written in *exponential notation*, with or without a *decimal point*:
  eg. `6.27, -2.4e30, 7e-5.`

- A scalar variable is declared via `my $variablename`, the `$` is **always** present. A variable name starts with a letter, and then may continue with any number of letters, digits or underscores! Every character in the name is significant, as is case.
- You can also write a scalar variable as `${variablename}`, just like in the Unix shell.
- A scalar variable can store any single scalar value:
  - An integer.
  - A real number (floating point).
  - An arbitrarily long string.
  - A reference to another variable.
- Integer literals may be written in decimal, octal or hexadecimal: eg. `-129, 0377 and 0xffe0.`
- Real literals may be written in *exponential notation*, with or without a *decimal point*:
  eg. `6.27, -2.4e30, 7e-5.`
- A string literal can be either delimited with single-quotes or double-quotes. Different rules apply inside the two kinds of string.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.
- Each character inside the quotes is placed into the string exactly as-is - even a literal newline!

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.
- Each character inside the quotes is placed into the string exactly as-is - even a literal newline!
- There are only two exceptions to this:
  - A single-quote on it's own would terminate the current string - to embed a single quote in a single-quoted string, write `\'`.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.
- Each character inside the quotes is placed into the string exactly as-is - even a literal newline!
- There are only two exceptions to this:
  - A single-quote on it's own would terminate the current string - to embed a single quote in a single-quoted string, write `\'`.
  - A backslash may be embedded in a single-quoted string as `\\`.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.
- Each character inside the quotes is placed into the string exactly as-is - even a literal newline!
- There are only two exceptions to this:
  - A single-quote on it's own would terminate the current string - to embed a single quote in a single-quoted string, write `\'`.
  - A backslash may be embedded in a single-quoted string as `\\`.
- Apart from these exceptions, nothing is modified inside a single quoted string.

- A single-quoted string, eg `'hello there'`, is an arbitrarily-long sequence of characters placed inside single quote marks.
- The quotes are not part of the string - rather, they *delimit* both ends of the string.
- The shortest (empty) single-quoted string is `''`.
- Each character inside the quotes is placed into the string exactly as-is - even a literal newline!
- There are only two exceptions to this:
  - A single-quote on it's own would terminate the current string - to embed a single quote in a single-quoted string, write `\'`.
  - A backslash may be embedded in a single-quoted string as `\\`.
- Apart from these exceptions, nothing is modified inside a single quoted string.
- In particular, `$` symbols are embedded as-is, and C-style escapes like `\n` do not function in a single-quoted string.

- A double-quoted string literal, like `"hello $name\n"`, is much more powerful. Again, it is an arbitrary sequence of characters which can be split across lines.

- A double-quoted string literal, like `"hello $name\n"`, is much more powerful. Again, it is an arbitrary sequence of characters which can be split across lines.
- However, the backslash can now specify several important control or *escape* operations as follows:

`\n`	Newline
`\t`	Tab
`\r`	Carriage Return
`\a`	Ring bell
`\072`	Any octal ASCII value (7*8+2 = 58 = ':')
`\x6d`	Any hexadecimal ASCII value (6*16+13 = 109 = 'm')
`\\`	Backslash
`\$`	Dollar
`\"`	A double-quote
`\l`	Lower-case the next letter
`\u`	Upper-case the next letter
`\L`	Start lower-casing the rest of the string
`\U`	Start upper-casing the rest of the string
`\E`	Stop `\L` or `\U`

- A double-quoted string literal, like `"hello $name\n"`, is much more powerful. Again, it is an arbitrary sequence of characters which can be split across lines.
- However, the backslash can now specify several important control or *escape* operations as follows:

`\n`	Newline
`\t`	Tab
`\r`	Carriage Return
`\a`	Ring bell
`\072`	Any octal ASCII value (7*8+2 = 58 = ':')
`\x6d`	Any hexadecimal ASCII value (6*16+13 = 109 = 'm')
`\\`	Backslash
`\$`	Dollar
`\"`	A double-quote
`\l`	Lower-case the next letter
`\u`	Upper-case the next letter
`\L`	Start lower-casing the rest of the string
`\U`	Start upper-casing the rest of the string
`\E`	Stop `\L` or `\U`

- For example, `"hello \Uthere\E how are you"` generates `"hello THERE how are you"`.

- A double-quoted string literal, like `"hello $name\n"`, is much more powerful. Again, it is an arbitrary sequence of characters which can be split across lines.
- However, the backslash can now specify several important control or *escape* operations as follows:

`\n`	Newline
`\t`	Tab
`\r`	Carriage Return
`\a`	Ring bell
`\072`	Any octal ASCII value (7*8+2 = 58 = ':')
`\x6d`	Any hexadecimal ASCII value (6*16+13 = 109 = 'm')
`\\`	Backslash
`\$`	Dollar
`\"`	A double-quote
`\l`	Lower-case the next letter
`\u`	Upper-case the next letter
`\L`	Start lower-casing the rest of the string
`\U`	Start upper-casing the rest of the string
`\E`	Stop `\L` or `\U`

- For example, `"hello \Uthere\E how are you"` generates `"hello THERE how are you"`.
- Also in a double-quoted string...

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.
- Example: `"hello $name\n"` is a string, comprising:
  - the character sequence `'hello '`,

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.
- Example: `"hello $name\n"` is a string, comprising:
  - the character sequence `'hello '`,
  - the current value of the variable `$name` (if `$name` is not in use, then the value is the undefined value, treated as the empty string),

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.
- Example: `"hello $name\n"` is a string, comprising:
  - the character sequence `'hello '`,
  - the current value of the variable `$name` (if `$name` is not in use, then the value is the undefined value, treated as the empty string),
  - the ASCII newline character (symbolically written as `\n`).

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.
- Example: `"hello $name\n"` is a string, comprising:
  - the character sequence `'hello '`,
  - the current value of the variable `$name` (if `$name` is not in use, then the value is the undefined value, treated as the empty string),
  - the ASCII newline character (symbolically written as `\n`).
- Suppose we wish to print the value of `$n` immediately followed by a sequence of characters that could also form part of the variable name. If we write:

  ```
  "you're the $nth person today..\n"
  ```

  Perl looks for a variable called `$nth`, and ends up interpolating the empty string, swallowing `th`!

- ...$ has a special meaning when followed by a variable name: Perl gathers the **longest possible** sequence of variable name characters, and replaces the entire sequence with the value of that variable.
- Example: `"hello $name\n"` is a string, comprising:
  - the character sequence `'hello '`,
  - the current value of the variable `$name` (if `$name` is not in use, then the value is the undefined value, treated as the empty string),
  - the ASCII newline character (symbolically written as `\n`).
- Suppose we wish to print the value of `$n` immediately followed by a sequence of characters that could also form part of the variable name. If we write:

  ```
  "you're the $nth person today..\n"
  ```

  Perl looks for a variable called `$nth`, and ends up interpolating the empty string, swallowing `th`!
- Fix: use `{}` around the variable name:

  ```
  "you're the ${n}th person today..\n"
  ```

- In double-quoted strings, you still need to backslash double quotes to embed them into a string. Choose your own quote character:

```
my $contentslink = qq!
<a href="$v.html">
   <img src="$v.png">
</a>
!;
```

- In double-quoted strings, you still need to backslash double quotes to embed them into a string. Choose your own quote character:

```
my $contentslink = qq!
<a href="$v.html">
   <img src="$v.png">
</a>
!;
```

- After the qq, the next character ('!') is taken as the quote character. All characters after this are placed into the string (with interpolations and backslashes working exactly as in a double-quoted string) until the next '!' is encountered.

- In double-quoted strings, you still need to backslash double quotes to embed them into a string. Choose your own quote character:

```
my $contentslink = qq!
<a href="$v.html">
   <img src="$v.png">
</a>
!;
```

- After the qq, the next character ('!') is taken as the quote character. All characters after this are placed into the string (with interpolations and backslashes working exactly as in a double-quoted string) until the next '!' is encountered.
- But now - you don't need to backslash double-quotes.

- In double-quoted strings, you still need to backslash double quotes to embed them into a string. Choose your own quote character:

```
my $contentslink = qq!
<a href="$v.html">
   <img src="$v.png">
</a>
!;
```

- After the qq, the next character ('!') is taken as the quote character. All characters after this are placed into the string (with interpolations and backslashes working exactly as in a double-quoted string) until the next '!' is encountered.
- But now - you don't need to backslash double-quotes.
- If the opening quote is an open bracket of some kind (round, curly or square), Perl uses the appropriate closing bracket as the closing quote - We could write the above as:

```
my $contentslink = qq(
<a href="$v.html">
   <img src="$v.png">
</a>
);
```

- Expressions in Perl are very like those of C, but without the pointer operators.

- Expressions in Perl are very like those of C, but without the pointer operators.
- Some operators expect numbers, others expect strings. Perl converts one to the other when needed. Thus the string `"17.3e7"` converts to the number `17.3e7` when needed, and the number `31.53` converts to the string `"31.53"` when needed.

- Expressions in Perl are very like those of C, but without the pointer operators.
- Some operators expect numbers, others expect strings. Perl converts one to the other when needed. Thus the string `"17.3e7"` converts to the number `17.3e7` when needed, and the number `31.53` converts to the string `"31.53"` when needed.
- Perl provides all the obvious **+**, **-**, *****, **/** arithmetic operators. Unlike C, *all operators operate in floating point*.

- Expressions in Perl are very like those of C, but without the pointer operators.
- Some operators expect numbers, others expect strings. Perl converts one to the other when needed. Thus the string `"17.3e7"` converts to the number `17.3e7` when needed, and the number `31.53` converts to the string `"31.53"` when needed.
- Perl provides all the obvious **+**, **-**, *****, **/** arithmetic operators. Unlike C, *all operators operate in floating point*.
- Unlike both C and Pascal, Perl provides the *exponentation operator* (written ******). For example: `3.25 ** 4` (ie. 3.25^4).

- Expressions in Perl are very like those of C, but without the pointer operators.
- Some operators expect numbers, others expect strings. Perl converts one to the other when needed. Thus the string `"17.3e7"` converts to the number `17.3e7` when needed, and the number `31.53` converts to the string `"31.53"` when needed.
- Perl provides all the obvious **+**, **-**, *****, **/** arithmetic operators. Unlike C, *all operators operate in floating point*.
- Unlike both C and Pascal, Perl provides the *exponentation operator* (written ******). For example: `3.25 ** 4` (ie. 3.25^4).
- Like C, Perl provides a *modulus* operator: 10%3 gives the remainder when 10 is divided by 3. Both values are truncated to integers before this operator is applied.

- Expressions in Perl are very like those of C, but without the pointer operators.
- Some operators expect numbers, others expect strings. Perl converts one to the other when needed. Thus the string `"17.3e7"` converts to the number `17.3e7` when needed, and the number `31.53` converts to the string `"31.53"` when needed.
- Perl provides all the obvious `+`, `-`, `*`, `/` arithmetic operators. Unlike C, *all operators operate in floating point*.
- Unlike both C and Pascal, Perl provides the *exponentation operator* (written `**`). For example: `3.25 ** 4` (ie. 3.25^4).
- Like C, Perl provides a *modulus* operator: `10%3` gives the remainder when 10 is divided by 3. Both values are truncated to integers before this operator is applied.
- Perl provides a set of numeric comparison operators just like C: `<`, `<=`, `==`, `>=`, `>` and `!=` (not equals).

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.
- A common mistake is comparing numbers with **eq** or strings with ==, allowed because strings and numbers are converted back and forth freely.

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.
- A common mistake is comparing numbers with **eq** or strings with ==, allowed because strings and numbers are converted back and forth freely.
- For example, `"0" == "000"` is true, but `0 eq "000"` is false. (The string `"0"` which is not the same as `"000"`!)

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.
- A common mistake is comparing numbers with **eq** or strings with ==, allowed because strings and numbers are converted back and forth freely.
- For example, `"0" == "000"` is true, but `0 eq "000"` is false. (The string `"0"` which is not the same as `"000"`!)
- Strings can be *concatenated* with the fullstop operator (**.**), eg:

```
"hello " . $name . "\n"
```

(Warning: No space is added automatically between the strings!)

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.
- A common mistake is comparing numbers with **eq** or strings with ==, allowed because strings and numbers are converted back and forth freely.
- For example, `"0" == "000"` is true, but `0 eq "000"` is false. (The string `"0"` which is not the same as `"000"`!)
- Strings can be *concatenated* with the fullstop operator (**.**), eg:

```
"hello " . $name . "\n"
```

  (Warning: No space is added automatically between the strings!)
- Concatenation is not used as much as you would expect - interpolation is often used instead. Write the above as:

```
"hello $name\n"
```

- Strings may be compared (alphabetically) via a separate set of comparison operators: **lt, le, eq, ge, gt** and **ne**.
- A common mistake is comparing numbers with **eq** or strings with ==, allowed because strings and numbers are converted back and forth freely.
- For example, `"0" == "000"` is true, but `0 eq "000"` is false. (The string `"0"` which is not the same as `"000"`!)
- Strings can be *concatenated* with the fullstop operator (**.**), eg:

  ```
  "hello " . $name . "\n"
  ```

  (Warning: No space is added automatically between the strings!)
- Concatenation is not used as much as you would expect - interpolation is often used instead. Write the above as:

  ```
  "hello $name\n"
  ```
- Another useful string operator is the *repetition* operator: `"fred" x 3` gives `"fredfredfred"`
  The right-hand argument is truncated to an integer before the replication occurs.

- The most vital operator of all is assignment (=). For example:

```
$x = 37;
$y = $x * 7 + 5;
$z = $z * 3;
```

  - The first simply sets $x to 37.

- The most vital operator of all is assignment (=). For example:

```
$x = 37;
$y = $x * 7 + 5;
$z = $z * 3;
```

  - The first simply sets `$x` to 37.
  - The second calculates `$x * 7 + 5` (using the current value of `$x`) and then stores the result in `$y`.

- The most vital operator of all is assignment (=). For example:

```
$x = 37;
$y = $x * 7 + 5;
$z = $z * 3;
```

  - The first simply sets `$x` to 37.
  - The second calculates `$x * 7 + 5` (using the current value of `$x`) and then stores the result in `$y`.
  - The last example takes the current value of $z, multiplies it by three, and stores the result back in $z.

- The most vital operator of all is assignment (=). For example:

```
$x = 37;
$y = $x * 7 + 5;
$z = $z * 3;
```

  - The first simply sets `$x` to 37.
  - The second calculates `$x * 7 + 5` (using the current value of `$x`) and then stores the result in `$y`.
  - The last example takes the current value of `$z`, multiplies it by three, and stores the result back in `$z`.

- An assignment also has a value, which means you can **nest** or **chain** assignments:

```
$y = 5 * ($a = 7 + $x);
$x = $y = 17;
```

  - The first example means: evaluate 7+`$x` and store the result in `$a`, then multiply `$a` by 5 and store the final result in `$y`.

- The most vital operator of all is assignment (=). For example:

```
$x = 37;
$y = $x * 7 + 5;
$z = $z * 3;
```

  - The first simply sets `$x` to 37.
  - The second calculates `$x * 7 + 5` (using the current value of `$x`) and then stores the result in `$y`.
  - The last example takes the current value of `$z`, multiplies it by three, and stores the result back in `$z`.

- An assignment also has a value, which means you can **nest** or **chain** assignments:

```
$y = 5 * ($a = 7 + $x);
$x = $y = 17;
```

  - The first example means: evaluate 7+`$x` and store the result in `$a`, then multiply `$a` by 5 and store the final result in `$y`.
  - The second example sets both `$x` and `$y` to 17.

- Perl (just like C) provides a set of assignment operators that modify a single variable:

- Perl (just like C) provides a set of assignment operators that modify a single variable:
- Nearly any binary operator that computes a value can have an = sign appended on the end. For instance:

```
$z *= 3;                    $sum += $element;
```

These read as *multiply z by 3*, *add element to sum*.

- Perl (just like C) provides a set of assignment operators that modify a single variable:
- Nearly any binary operator that computes a value can have an = sign appended on the end. For instance:

```
$z *= 3;                    $sum += $element;
```

  These read as *multiply z by 3*, *add element to sum*.
- The same works for strings: `$z .= $a` appends the contents of `$a` onto the end of `$z`.

- Perl (just like C) provides a set of assignment operators that modify a single variable:
- Nearly any binary operator that computes a value can have an = sign appended on the end. For instance:

```
$z *= 3;                    $sum += $element;
```

  These read as *multiply z by 3*, *add element to sum*.
- The same works for strings: `$z .= $a` appends the contents of `$a` onto the end of `$z`.
- Just like basic assignment, all the binary assignment operators return a value too. So the following is valid:

```
$a = 3;
$b = ($a += 4) * 7;
```

- Perl (just like C) provides a set of assignment operators that modify a single variable:
- Nearly any binary operator that computes a value can have an = sign appended on the end. For instance:

```
$z *= 3;                    $sum += $element;
```

  These read as *multiply z by 3*, *add element to sum*.
- The same works for strings: `$z .= $a` appends the contents of `$a` onto the end of `$z`.
- Just like basic assignment, all the binary assignment operators return a value too. So the following is valid:

```
$a = 3;
$b = ($a += 4) * 7;
```

- **However**, never change the same variable inside two branches of the same expression:

```
$a = 3;
$b = ($a += 4) * ($a -= 2);
```

- To *increment* or *decrement* $a, write:

```
$a++;
```

```
$a--;
```

- To *increment* or *decrement* `$a`, write:

```
$a++;                    $a--;
```

- Perl has a prefix and postfix form of these operators: `++$a`, `$a++`, `--$a` and `$a--`. Both forms increment (or decrement) the variable in the same way.

- To *increment* or *decrement* $a, write:

```
$a++;                                   $a--;
```

- Perl has a prefix and postfix form of these operators: ++$a, $a++, --$a and $a--. Both forms increment (or decrement) the variable in the same way.
- Difference: when embedding in a large expression, old or new value? Consider the following two examples, first:

Perl	Simplified Form	Effect
`$a = 7;`	a=7	a:7
`$b = ++$a;`	a++; b=a	a:8, b:8
`$c = $b--;`	c=b; b--	c:8, b:7

- To *increment* or *decrement* $a, write:

```
$a++;                                   $a--;
```

- Perl has a prefix and postfix form of these operators: ++$a, $a++, --$a and $a--. Both forms increment (or decrement) the variable in the same way.
- Difference: when embedding in a large expression, old or new value? Consider the following two examples, first:

Perl	Simplified Form	Effect
$a = 7;	a=7	a:7
$b = ++$a;	a++; b=a	a:8, b:8
$c = $b--;	c=b; b--	c:8, b:7

- Second:

Perl	Simplified	Effect
$a = 7;	a=7	a:7
$b = $a++;	b=a; a++	b:7, a:8
$c = --$b;	b--; c=b	b:6, c:6

In both cases, $a ends up as 8.

- Expressions used in a boolean context are evaluated in the usual way as numbers or strings.

- Expressions used in a boolean context are evaluated in the usual way as numbers or strings.
- When the result value is produced (a number or a string), a *zero value or empty string* means *false*, and *anything else is true!*

There are a few extra boolean operators:

- ! is a unary operator meaning *not*.

- Expressions used in a boolean context are evaluated in the usual way as numbers or strings.
- When the result value is produced (a number or a string), a *zero value or empty string* means *false*, and *anything else is true!*

There are a few extra boolean operators:

- `!` is a unary operator meaning *not*.
- `||` and `&&` come straight from C – these can be written as `or` and `and` in modern Perl (but with rather confusing precedences).

- Expressions used in a boolean context are evaluated in the usual way as numbers or strings.
- When the result value is produced (a number or a string), a *zero value or empty string* means *false*, and *anything else is true!*

There are a few extra boolean operators:

- `!` is a unary operator meaning *not*.
- `||` and `&&` come straight from C – these can be written as `or` and `and` in modern Perl (but with rather confusing precedences).
- Just like C and Java (but unlike Pascal), they *short-circuit*:
  - Consider:
    `$a < 7 || $b > 6`
    If `$a` is less than 7, then the whole expression is bound to be true. There is no point in evaluating the rest of the expression - so Perl doesn't!

- Expressions used in a boolean context are evaluated in the usual way as numbers or strings.
- When the result value is produced (a number or a string), a *zero value or empty string* means *false*, and *anything else is true!*

There are a few extra boolean operators:

- `!` is a unary operator meaning *not*.
- `||` and `&&` come straight from C – these can be written as `or` and `and` in modern Perl (but with rather confusing precedences).
- Just like C and Java (but unlike Pascal), they *short-circuit*:
  - Consider:
    `$a < 7 || $b > 6`
    If `$a` is less than 7, then the whole expression is bound to be true. There is no point in evaluating the rest of the expression - so Perl doesn't!
  - Similarly, consider:
    `$s eq "hello" && $t ne "bonjour"`
    If `$s` is not `"hello"` then the whole expression must be false. Again, there's absolutely no point in evaluating the second half.

- Any expression can become a statement by appending '`;`': `3;` means *evaluate expression* (result: 3) and *discard the result*.

- Any expression can become a statement by appending `';'`: `3;` means *evaluate expression* (result: 3) and *discard the result*.
- Usually, expression-statements have side-effects:
  - Assignments (the basic =, all the binary assignment operators like *=, and the ++ and -- operators).

- Any expression can become a statement by appending `';'`: `3;` means *evaluate expression* (result: 3) and *discard the result*.
- Usually, expression-statements have side-effects:
  - Assignments (the basic =, all the binary assignment operators like *=, and the ++ and -- operators).
  - Procedure/subroutine calls (eg. print - or your own procedures).

- Any expression can become a statement by appending `';'`: `3;` means *evaluate expression* (result: 3) and *discard the result*.
- Usually, expression-statements have side-effects:
  - Assignments (the basic =, all the binary assignment operators like *=, and the ++ and -- operators).
  - Procedure/subroutine calls (eg. print - or your own procedures).
- Perl also provides *modifiers* for single statements:

```
<statement> if <expr> ;
<statement> unless <expr> ;
<statement> while <expr> ;
<statement> until <expr> ;
```

(Perl allows `unless` to be used as a synonym for `if !`, ie. *if not true*, and `until` as a synonym for `while !`).

- Any expression can become a statement by appending '`;`': `3;` means *evaluate expression* (result: 3) and *discard the result*.
- Usually, expression-statements have side-effects:
  - Assignments (the basic =, all the binary assignment operators like *=, and the ++ and -- operators).
  - Procedure/subroutine calls (eg. print - or your own procedures).
- Perl also provides *modifiers* for single statements:

```
<statement> if <expr> ;
<statement> unless <expr> ;
<statement> while <expr> ;
<statement> until <expr> ;
```

  (Perl allows `unless` to be used as a synonym for `if !`, ie. *if not true*, and `until` as a synonym for `while !`).
- A sequence of statements may be enclosed inside `{}` braces forming a *block*. NB: no '`;`' after the '`}`' of a block.

- Perl provides a conventional **if.. elsif.. elsif.... else** statement, to choose between two or more alternatives:

```
if( $i < 20 || $j > 7.4 )
{
        print "case one\n";
} elsif( $i > 40 && $j > 0 )
{
        print "case two\n";
} else
{
        print "case three\n";
}
```

Note that the brackets – both round and curly – are compulsory on an **if** - and the loop below.

- Perl provides a conventional **if.. elsif.. elsif.... else** statement, to choose between two or more alternatives:

```
if( $i < 20 || $j > 7.4 )
{
        print "case one\n";
} elsif( $i > 40 && $j > 0 )
{
        print "case two\n";
} else
{
        print "case three\n";
}
```

  Note that the brackets – both round and curly – are compulsory on an **if** - and the loop below.

- In a rare omission, Perl did **NOT** provide a special case/switch statement for multi-way comparisons. An add-on module adds this.

- Perl provides a conventional **if.. elsif.. elsif.... else** statement, to choose between two or more alternatives:

```
if( $i < 20 || $j > 7.4 )
{
        print "case one\n";
} elsif( $i > 40 && $j > 0 )
{
        print "case two\n";
} else
{
        print "case three\n";
}
```

  Note that the brackets – both round and curly – are compulsory on an **if** - and the loop below.

- In a rare omission, Perl did **NOT** provide a special case/switch statement for multi-way comparisons. An add-on module adds this.
- Perl also provides a conventional *test at the top* while loop:

```
my $w = $x; my $h = 1;
while ( abs($w-$h) > 0.001 )
{
        $w = ($w+$h)/2;
        $h = $x/$w;
}
```

- Perl provides a conventional **if.. elsif.. elsif.... else** statement, to choose between two or more alternatives:

```
if( $i < 20 || $j > 7.4 )
{
        print "case one\n";
} elsif( $i > 40 && $j > 0 )
{
        print "case two\n";
} else
{
        print "case three\n";
}
```

  Note that the brackets – both round and curly – are compulsory on an **if** - and the loop below.

- In a rare omission, Perl did **NOT** provide a special case/switch statement for multi-way comparisons. An add-on module adds this.
- Perl also provides a conventional *test at the top* while loop:

```
my $w = $x; my $h = 1;
while ( abs($w-$h) > 0.001 )
{
        $w = ($w+$h)/2;
        $h = $x/$w;
}
```

- The above algorithm happens to find the square root of $x!

- Perl provides a *test at the bottom* loop, two forms:

```
do {
        $y *= $x;
        $x += 2;
} while( $x < 15 );
```

```
do {
        $y *= $x;
        $x += 2;
} until( $x >= 15 );
```

- Perl provides a *test at the bottom* loop, two forms:

```
do {
        $y *= $x;
        $x += 2;
} while( $x < 15 );
```

```
do {
        $y *= $x;
        $x += 2;
} until( $x >= 15 );
```

- A C-style *counting loop*:

```
for( my $sum = 0, my $i = 1; $i <= 10; $i++ )
{
        $sum += $i;
}
```

- Perl provides a *test at the bottom* loop, two forms:

```
do {
        $y *= $x;
        $x += 2;
} while( $x < 15 );
```

```
do {
        $y *= $x;
        $x += 2;
} until( $x >= 15 );
```

- A C-style *counting loop*:

```
for( my $sum = 0, my $i = 1; $i <= 10; $i++ )
{
        $sum += $i;
}
```

- A very useful *for each element in a list/array* loop:

```
foreach my $x ( 1, 3, 7, 5, 4, 54 )
{
        $total += $x;
}
```

(We'll see more about arrays next session).

- Perl provides a *test at the bottom* loop, two forms:

```
do {
        $y *= $x;
        $x += 2;
} while( $x < 15 );
```

```
do {
        $y *= $x;
        $x += 2;
} until( $x >= 15 );
```

- A C-style *counting loop*:

```
for( my $sum = 0, my $i = 1; $i <= 10; $i++ )
{
        $sum += $i;
}
```

- A very useful *for each element in a list/array* loop:

```
foreach my $x ( 1, 3, 7, 5, 4, 54 )
{
        $total += $x;
}
```

(We'll see more about arrays next session).

- Exercise: Try writing a little Perl program that reads in a number and computes the square root using the while loop on the previous slide, printing out a message like `"The square root of $x is $w"`.

Lets consider getting input from the keyboard, and reporting results to the screen.

- The <> operator (pronounced *diamond* or *getline*) fetches a line of input from a filehandle - `STDIN` is a filehandle, represents the standard input. So:

  ```
  $name = <STDIN>;
  ```

  reads an entire line of input, up to and including a newline, and then stores the input in the variable (including the newline).

Lets consider getting input from the keyboard, and reporting results to the screen.

- The <> operator (pronounced *diamond* or *getline*) fetches a line of input from a filehandle - `STDIN` is a filehandle, represents the standard input. So:

  ```
  $name = <STDIN>;
  ```

  reads an entire line of input, up to and including a newline, and then stores the input in the variable (including the newline).
- After reading a line, you usually want to get rid of the trailing newline. Two operators:
  - Perl 4 provided `chop($name)` which removes the last character from the named variable and returns the character removed.

Lets consider getting input from the keyboard, and reporting results to the screen.

- The <> operator (pronounced *diamond* or *getline*) fetches a line of input from a filehandle - `STDIN` is a filehandle, represents the standard input. So:

  ```
  $name = <STDIN>;
  ```

  reads an entire line of input, up to and including a newline, and then stores the input in the variable (including the newline).
- After reading a line, you usually want to get rid of the trailing newline. Two operators:
  - Perl 4 provided `chop($name)` which removes the last character from the named variable and returns the character removed.
  - Perl 5 added `chomp($name)` which deletes a trailing newline or does nothing.

Lets consider getting input from the keyboard, and reporting results to the screen.

- The <> operator (pronounced *diamond* or *getline*) fetches a line of input from a filehandle - `STDIN` is a filehandle, represents the standard input. So:

  ```
  $name = <STDIN>;
  ```

  reads an entire line of input, up to and including a newline, and then stores the input in the variable (including the newline).
- After reading a line, you usually want to get rid of the trailing newline. Two operators:
  - Perl 4 provided `chop($name)` which removes the last character from the named variable and returns the character removed.
  - Perl 5 added `chomp($name)` which deletes a trailing newline or does nothing.
- Use `chomp` everywhere; it's safer and more portable (it will remove the newline from the string even if the newline convention on the OS you're using is not a single character!).

- There is a nice simple way of printing some results:

```
print expression;
```

- There is a nice simple way of printing some results:

```
print expression;
```

- Combined with the variable interpolation we've seen in strings, this gives us all the formatting power we need for now:

```
print "debug: x=$x, y=$y, z=$z\n";
```

- There is a nice simple way of printing some results:

```
print expression;
```

- Combined with the variable interpolation we've seen in strings, this gives us all the formatting power we need for now:

```
print "debug: x=$x, y=$y, z=$z\n";
```

- Here's an example (**eg1**), allowing you to investigate different expressions:

```
print "Please enter x: ";
my $x = <STDIN>;
chomp $x;
print "Please enter y: ";
my $y = <STDIN>;
chomp $y;
my $z = $x + $y;
print "\n$x + $y = $z\n";
```

- There is a nice simple way of printing some results:

```
print expression;
```

- Combined with the variable interpolation we've seen in strings, this gives us all the formatting power we need for now:

```
print "debug: x=$x, y=$y, z=$z\n";
```

- Here's an example (**eg1**), allowing you to investigate different expressions:

```
print "Please enter x: ";
my $x = <STDIN>;
chomp $x;
print "Please enter y: ";
my $y = <STDIN>;
chomp $y;
my $z = $x + $y;
print "\n$x + $y = $z\n";
```

- You may like to spend some time trying some examples of expressions, starting with the above example and incorporating different, more complex, expressions.

- There is a nice simple way of printing some results:

```
print expression;
```

- Combined with the variable interpolation we've seen in strings, this gives us all the formatting power we need for now:

```
print "debug: x=$x, y=$y, z=$z\n";
```

- Here's an example (**eg1**), allowing you to investigate different expressions:

```
print "Please enter x: ";
my $x = <STDIN>;
chomp $x;
print "Please enter y: ";
my $y = <STDIN>;
chomp $y;
my $z = $x + $y;
print "\n$x + $y = $z\n";
```

- You may like to spend some time trying some examples of expressions, starting with the above example and incorporating different, more complex, expressions.
- Try various += and ++ types of operators to get clear exactly what they do.

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!
- So does the keyboard: On Unix systems, end-of-input is signalled by the user typing CTRL-D on a line on its own.

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!
- So does the keyboard: On Unix systems, end-of-input is signalled by the user typing CTRL-D on a line on its own.
- No CTRL-D character (ASCII code 4) is delivered; CTRL-D is a signal that input has ended.

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!
- So does the keyboard: On Unix systems, end-of-input is signalled by the user typing CTRL-D on a line on its own.
- No CTRL-D character (ASCII code 4) is delivered; CTRL-D is a signal that input has ended.
- When eof occurs, <> returns the *empty string*. This never otherwise occurs - why?

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!
- So does the keyboard: On Unix systems, end-of-input is signalled by the user typing CTRL-D on a line on its own.
- No CTRL-D character (ASCII code 4) is delivered; CTRL-D is a signal that input has ended.
- When eof occurs, <> returns the *empty string*. This never otherwise occurs - why?
- So comparing the result of <> against the empty string will reliably determine eof:

```
if( $line eq "" )...
```

- We've seen that `$line = <STDIN>` reads a whole line of input from stdin (normally keyboard).
- But what if there's no more input? Files have a concept of *end of file (eof)* - after you have read the last line of data!
- So does the keyboard: On Unix systems, end-of-input is signalled by the user typing CTRL-D on a line on its own.
- No CTRL-D character (ASCII code 4) is delivered; CTRL-D is a signal that input has ended.
- When eof occurs, <> returns the *empty string*. This never otherwise occurs - why?
- So comparing the result of <> against the empty string will reliably determine eof:

```
if( $line eq "" )...
```

- More typically, you test for *not eof*, which is written `if( $line ne "" )` or `if( $line )`.

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- Using a `while` instead, and adding `my` to declare `$line`, gives us the **for each line in a file** idiom:

```
while( my $line = <STDIN> )   # for each line from stdin
{
        chomp $line;
        # now process $line
}
```

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- Using a `while` instead, and adding `my` to declare `$line`, gives us the **for each line in a file** idiom:

```
while( my $line = <STDIN> )   # for each line from stdin
{
        chomp $line;
        # now process $line
}
```

- Let's see an simple example of that (**eg2**):

  Write a program that reads a list of numbers (one per line) from `STDIN`*, adds all these numbers up, and prints the total.*

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- Using a `while` instead, and adding `my` to declare `$line`, gives us the **for each line in a file** idiom:

```
while( my $line = <STDIN> )   # for each line from stdin
{
        chomp $line;
        # now process $line
}
```

- Let's see an simple example of that (**eg2**):

  Write a program that reads a list of numbers (one per line) from `STDIN`*, adds all these numbers up, and prints the total.*

- Above the while loop, we initialize: `my $sum = 0;`

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- Using a `while` instead, and adding `my` to declare `$line`, gives us the **for each line in a file** idiom:

```
while( my $line = <STDIN> )   # for each line from stdin
{
        chomp $line;
        # now process $line
}
```

- Let's see an simple example of that (**eg2**):

  Write a program that reads a list of numbers (one per line) from `STDIN`*, adds all these numbers up, and prints the total.*

- Above the while loop, we initialize: `my $sum = 0;`
- Processing is: `$sum += $line;`

- We can even combine the line reading, assignment, and test for not eof into:

```
if( $line = <STDIN> )   # if we've read a line..
```

- Using a `while` instead, and adding `my` to declare `$line`, gives us the **for each line in a file** idiom:

```
while( my $line = <STDIN> )   # for each line from stdin
{
        chomp $line;
        # now process $line
}
```

- Let's see an simple example of that (**eg2**):

  Write a program that reads a list of numbers (one per line) from `STDIN`*, adds all these numbers up, and prints the total.*

- Above the while loop, we initialize: `my $sum = 0;`
- Processing is: `$sum += $line;`
- At the end, add `print "total: $sum\n"`.

- Perl can read the contents of named files (or Unix pipelines), create/overwrite a named file with new contents, and append new output on the end of a file.

- Perl can read the contents of named files (or Unix pipelines), create/overwrite a named file with new contents, and append new output on the end of a file.
- Suppose we wish to read a file called `fred`. The first step is to create a filehandle like `STDIN` but connected to the file `"fred"`:

- Perl can read the contents of named files (or Unix pipelines), create/overwrite a named file with new contents, and append new output on the end of a file.
- Suppose we wish to read a file called `fred`. The first step is to create a filehandle like `STDIN` but connected to the file `"fred"`:
- Near the top of our program, we write:

```
use IO::File;
```

- Perl can read the contents of named files (or Unix pipelines), create/overwrite a named file with new contents, and append new output on the end of a file.
- Suppose we wish to read a file called `fred`. The first step is to create a filehandle like `STDIN` but connected to the file `"fred"`:
- Near the top of our program, we write:

```
use IO::File;
```

- Then to open `fred`:

```
my $in = new IO::File( "fred" );
unless( $in )
{
        # ... handle the failure...
}
```

If the file `"fred"` doesn't already exist, **new IO::File** will fail, returning 0 - a boolean false - so check for success by testing the result. Or check for failure by testing `unless( $in )`.

- Perl can read the contents of named files (or Unix pipelines), create/overwrite a named file with new contents, and append new output on the end of a file.
- Suppose we wish to read a file called `fred`. The first step is to create a filehandle like `STDIN` but connected to the file `"fred"`:
- Near the top of our program, we write:

```
use IO::File;
```

- Then to open `fred`:

```
my $in = new IO::File( "fred" );
unless( $in )
{
        # ... handle the failure...
}
```

  If the file `"fred"` doesn't already exist, **new IO::File** will fail, returning 0 - a boolean false - so check for success by testing the result. Or check for failure by testing `unless( $in )`.
- Often, handling the failure is done by printing an error message (on `STDERR`) and exiting - use `die`:

```
my $in = new IO::File( "fred" );
unless( $in )
{
        die "can't open fred\n";
}
```

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Best of all, we can use the common *Do or die* idiom. This wouldn't work without short-circuit evaluation:

```
my $in = new IO::File( "fred" ) || die "can't open fred!\n";
```

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Best of all, we can use the common *Do or die* idiom. This wouldn't work without short-circuit evaluation:

```
my $in = new IO::File( "fred" ) || die "can't open fred!\n";
```

- Now, `$in` is an open filehandle, just like `STDIN`, from which we can read data.

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Best of all, we can use the common *Do or die* idiom. This wouldn't work without short-circuit evaluation:

```
my $in = new IO::File( "fred" ) || die "can't open fred!\n";
```

- Now, `$in` is an open filehandle, just like `STDIN`, from which we can read data.
- `$line = <$in>` reads the next line of input from `fred`. When there is no more input, `$line` will contain the empty string.

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Best of all, we can use the common *Do or die* idiom. This wouldn't work without short-circuit evaluation:

```
my $in = new IO::File( "fred" ) || die "can't open fred!\n";
```

- Now, `$in` is an open filehandle, just like `STDIN`, from which we can read data.
- `$line = <$in>` reads the next line of input from `fred`. When there is no more input, `$line` will contain the empty string.
- A typical *read every line* program looks like **eg3**:

```
use IO::File;
my $in = new IO::File( "fred" ) || die "can't open fred\n";
while( my $line = <$in> )
{
        chomp $line;
        print "read '$line'\n";
}
$in->close;
```

- Better still, use conditional modifier syntax:

```
my $in = new IO::File( "fred" );
die "can't open fred\n" unless $in;
```

- Best of all, we can use the common *Do or die* idiom. This wouldn't work without short-circuit evaluation:

```
my $in = new IO::File( "fred" ) || die "can't open fred!\n";
```

- Now, `$in` is an open filehandle, just like `STDIN`, from which we can read data.
- `$line = <$in>` reads the next line of input from `fred`. When there is no more input, `$line` will contain the empty string.
- A typical *read every line* program looks like **eg3**:

```
use IO::File;
my $in = new IO::File( "fred" ) || die "can't open fred\n";
while( my $line = <$in> )
{
        chomp $line;
        print "read '$line'\n";
}
$in->close;
```

- Note: As well as `die` there's a function `warn` which prints a message to `STDERR` but doesn't exit.

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- We may now write new data into bob by any number of:

```
print $out "...some data...\n"; or $out->print( "...some data...\n" );
```

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- We may now write new data into bob by any number of:

```
print $out "...some data...\n"; or $out->print( "...some data...\n" );
```

- Just as with reading, don't forget to `$out->close` when you finish writing data.

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- We may now write new data into bob by any number of:

```
print $out "...some data...\n"; or $out->print( "...some data...\n" );
```

- Just as with reading, don't forget to `$out->close` when you finish writing data.
- We can append data to bob, instead of overwriting:

```
my $out = new IO::File( ">> bob" ) || die "sob.. no bob\n";
```

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- We may now write new data into bob by any number of:

```
print $out "...some data...\n"; or $out->print( "...some data...\n" );
```

- Just as with reading, don't forget to `$out->close` when you finish writing data.
- We can append data to bob, instead of overwriting:

```
my $out = new IO::File( ">> bob" ) || die "sob.. no bob\n";
```

- You can also open a pipe to/from a Unix pipeline for reading/writing:
  - `my $in = new IO::File( "ls | sort -r |" );`
    If the last character is a '|', then we can read data from the pipeline: Any output that `ls | sort -r` prints onto its STDOUT will be available for us to read via `<$in>`.

- To open a file for writing (overwriting the old contents):

```
my $out = new IO::File( "> bob" ) || die "sob.. no bob\n";
```

- We may now write new data into bob by any number of:

```
print $out "...some data...\n"; or $out->print( "...some data...\n" );
```

- Just as with reading, don't forget to `$out->close` when you finish writing data.
- We can append data to bob, instead of overwriting:

```
my $out = new IO::File( ">> bob" ) || die "sob.. no bob\n";
```

- You can also open a pipe to/from a Unix pipeline for reading/writing:
  - `my $in = new IO::File( "ls | sort -r |" );`
    If the last character is a '|', then we can read data from the pipeline: Any output that `ls | sort -r` prints onto its STDOUT will be available for us to read via `<$in>`.
  - `my $out = new IO::File( "| expand" );`
    If the first character is a '|', then we can write data to the pipe: `expand` will perceive a stream of data coming from its STDIN, but it'll really be whatever we write to `$out`.

- Exercise: Merge **eg2** and **eg3** to sum up the leading numbers in a specific named file.
- Exercise: Write a program that reads every line from `STDIN`, lower-cases it using `lc()` and writes the lower-cased lines into a file called `lower`. You might call such a program `mklower`.
- Exercise: modify `mklower` slightly: remove the word `STDIN` from the `<STDIN>` getline call, leaving the mysterious syntax `<>`. We'll explain next session what this syntax means - for now, try to work it out for yourself by experimenting with `mklower`'s behaviour.